

National Garage

# Merlin "E" Series Programming Guide



Genuine E960M

The E960M remote control is capable of operating motors that use the older Security+ encryption, as well as motors that are using the newer Security+ 2.0

The remote control is preset for Security+ 2.0 so if you have a EVO or MYQ Merlin motors, simply code normally as below.

## Programming Your Remote Control - Security+ 2.0

- 1 Locate the Learn Button on your motor
- 2 Press and hold any button on the remote control or wireless wall control. The LED on the opener will begin to flash
- 3 Press and immediately release the Learn button
- 4 The opener light flashes or 2 clicks are heard when it has learnt the code
- 5 Test the operation of your new remote control

### Programming Your Remote Control - Security+

- 1 Press the left and right buttons on the remote simutaniously until the LED on the remote stays solid.
- 2 Press & release the Learn button on your motor. You now have 30 seconds to program in your remote control.

3 Press and release (2 secs) any button on the remote control. If the motor's light flashes, your remote control has been programmed in. Move to step 5.

4 If it does not flash, press and release the same button on your remote control again. Once the motor's light flashes, do not press the remote button again.

- 5 Press any one of the other three buttons. This 'Locks' in the code to your button that were pressing in steps 3/4.
- 6 Test the operation of your new remote control.

### **Clearing The Codes From Your Motor**

- 1 Press and hold the Learn button for 6 seconds, or until the LED goes out
- 2 Test that your remote no longer operates the motor
  - Please note, this will clear every remote programmed into the motor

For technical support, see our website below.

Please have the model number of your remote control and garage / gate opener before calling.

#### www.ngro.com.au