


# Merlin<sup>®</sup>



[gomerlin.com.au](http://gomerlin.com.au)

[gomerlin.co.nz](http://gomerlin.co.nz)




## Commander Elite II MS107MYQ

### Sectional and Tilt Garage Door Opener Installation and Operating Instructions



Australia



New Zealand

Owners Copy: SAVE THESE INSTRUCTIONS for future reference



This manual contains IMPORTANT SAFETY information  
DO NOT PROCEED WITH THE INSTALLATION BEFORE READING THOROUGHLY



# SAFETY INSTRUCTIONS

## WARNING

- Failure to comply with the following instructions may result in serious injury or property damage.
- Read and follow all instructions carefully.
- The garage door opener is designed and tested to offer safe service provided it is installed and operated in strict accordance with the instructions in this manual.



These safety alert symbols mean **WARNING** : A possible risk to personal safety or property damage exists.



**Keep the garage door balanced.** Do not let the garage door opener compensate for a binding or sticking garage door. Sticking, binding or unbalanced doors must be repaired before installing this opener.



**Do not wear rings, watches or loose clothing** while installing or servicing a garage door opener. Wear gloves and suitable protective clothing where appropriate.



**Frequently examine the door installation.** In particular examine cable, springs and mountings for signs of wear, damage or imbalance. Do not use if repair or adjustment is needed since springs and hardware are under extreme tension and a fault can cause serious personal injury.



To avoid serious injury from entanglement, **remove all ropes, chains and locks connected to the garage door** before installing the door opener.



**Installation and wiring** must be in compliance with your local building and electrical codes.



**The safety reverse system test is very important.** Your garage door **MUST** reverse on contact with a 40 mm obstacle placed on the floor. Failure to properly adjust the opener may result in serious injury from a closing garage door. **Repeat the test once a month and make any necessary adjustments.**



This appliance should not be used by children or persons with reduced physical, sensory or mental capabilities, or a lack of experience & knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.



**Automatic Drive** - Keep away from the area of the door as it may operate unexpectedly.



**WARNING!** Product includes wireless transmitters and wall controls that contain coin/button cell batteries. Keep wireless devices and batteries away from children. Battery can cause severe or fatal injuries in 2 hours or less if swallowed or placed inside any part of the body. Seek immediate medical attention if it is suspected that a coin/button cell battery has been swallowed or placed inside any part of the body.



**The opener must not be used on a wicket door (door within a door).**



**The Protector System™ (IR Beams) must be used for all installations where the closing force as measured on the bottom of the door is over 400 N (40 kgf).**

Excessive force will interfere with the proper operation of the safety reverse system or damage the garage door.

**Installers must ensure that the doors are installed in a compliant manner as per AS/NZS 60335.2.95.**



**After installation, ensure that the parts of the door do not extend over public footpaths or roads.**



Install the wireless wall control (or any additional wall control) **in a location where the garage door is visible, away from moving parts, at a height of at least 1.5 m and out of the reach of children. Do not allow children to operate push buttons or transmitters.** Serious personal injury from a closing garage door may result from misuse of the opener.



**Permanently fasten the warning labels in prominent places,** adjacent to wall controls and manual release mechanisms as a reminder of safe operating procedures.



**Activate opener only when the door is in full view, free of obstructions and the opener is properly adjusted. No one should enter or leave the garage while the door is in motion.**



**Do not allow children to play near the door or with door controls.**



If the power cable is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid hazard.



**Disconnect electric power to the garage door opener before making repairs or removing covers.**



**This opener should not be installed in a damp or wet space exposed to weather.**

**KEEP THESE INSTRUCTIONS**

**NOTE: If your garage has no service entrance door, we recommend an outside quick release must be installed. This accessory allows manual operation of the garage door from outside in case of power failure.**

| CONTENTS               | PAGE  |
|------------------------|-------|
| SAFETY INSTRUCTIONS    | 2     |
| BEFORE YOU BEGIN       | 3     |
| DOOR TYPES             | 3     |
| CARTON INVENTORY       | 4     |
| RAIL SIZES             | 4     |
| TOOLS REQUIRED         | 5     |
| HARDWARE PROVIDED      | 5     |
| COMPLETED INSTALLATION | 5     |
| CONTROL PANEL          | 6     |
| ASSEMBLY               | 7     |
| INSTALLATION           | 8-11  |
| OPERATE MANUAL RELEASE | 11    |
| ADJUSTMENT             | 12-13 |

|                                             |       |
|---------------------------------------------|-------|
| INSTALL THE PROTECTOR SYSTEM (OPTIONAL)     | 13    |
| PROGRAM TRANSMITTER TO OPERATE OPENER LIGHT | 14    |
| TIMER TO CLOSE                              | 15    |
| INSTALL WARNING LABELS                      | 16    |
| PARTIAL OPENING FEATURE                     | 16    |
| WIRELESS PROGRAMMING                        | 17    |
| USING YOUR OPENER                           | 18    |
| CARE OF YOUR OPENER                         | 18    |
| REPLACE BATTERIES IN TRANSMITTER            | 18    |
| ACCESSORIES                                 | 19-21 |
| TROUBLESHOOTING                             | 21-22 |
| SPECIFICATIONS                              | 23    |
| WARRANTY                                    | 24    |

# INTRODUCTION

## BEFORE YOU BEGIN:


1. Look at the wall and ceiling above the garage door. (The opener and header bracket must be securely fastened to structural supports).
2. Do you have a finished ceiling in your garage? If so, a support bracket and additional fastening hardware (not supplied) may be required.
3. Is there a separate access door in addition to the garage door? If not, model E1702M Outside Quick Release Accessory is required. This accessory allows manual operation of the garage door from outside in case of power or mechanical failure.
4. Complete the following test to make sure your garage door is balanced and is not sticking or binding:
  - Lift the door about halfway. Release the door. If balanced, it should stay in place, supported entirely by its springs.
  - Raise and lower the door to check for any binding or sticking. The maximum allowable force to move the door in any position is 20 kgf (20kg's). If the door binds, sticks, or appears out of balance, discontinue use and contact a trained door technician immediately.

## 1 DOOR TYPES

- A. Sectional Door with curved track
- B. One-Piece Door with Horizontal Track Only
- C. One-Piece Door without track
- D. J-Type tilt Door fittings

**NOTE:** When installing an opener on J-Type (D) tilt doors, ensure the PIVOT POSITION No. 1 is used. Pivot positions 2 and 3 progressively increase the force required to operate the door and are not recommended, or approved with this opener.

**To suit spring balanced Residential Sectional and Tilt doors up to 20.0 m<sup>2</sup>.**



### Electrical Connection

A 240 V General Purpose Outlet (GPO) ie. Power Point must be available in close proximity to the powerhead. This fitting is not part of the Opener hardware and must be supplied by the consumer.



In the event of a power outage or the unit being disconnected from the power source, the door **MUST** be operated and supervised so that it completes a full UP and DOWN cycle with no obstructions in place to ensure that the unit automatically checks that the safety force settings are correct.

# INTRODUCTION


## 2 CARTON INVENTORY

Your garage door opener and rail are packed in two separate cartons. The Commander Elite II MS107MYQ opener carton contains the opener, its fitting hardware and accessories. The rail carton contains the rail and some hardware.

### Rails:

Different length rails (2.2 m & 2.5 m) are available for different height doors, ensure you have the correct one.

- |                                                         |                           |
|---------------------------------------------------------|---------------------------|
| 1. Opener                                               | 8. Door bracket           |
| 2. E975M four button remote control (2)                 | 9. Hardware bag           |
| 3. E148M four button wireless wall mount remote control | 10. C-Rail bracket (2)    |
| 4. Curved door arm                                      | 11. Tilt door bracket     |
| 5. Hanging bracket (2)                                  | 12. Quick Reference Guide |
| 6. Rail bracket                                         | 13. Warning labels        |
| 7. Header bracket                                       | 14. Rail assembly         |



## 3 RAIL SIZES AVAILABLE

| DOOR HEIGHT:<br>Sectional Doors | BELT & RAIL PART<br>NUMBER: | RAIL LENGTH:         | CEILING FIXING<br>POINTS: | ALTERNATE FIXING<br>POINT: |
|---------------------------------|-----------------------------|----------------------|---------------------------|----------------------------|
| Up to 2.2 m                     | 8022 CR5                    | 3000 mm single piece | 2840 mm                   | 2950 mm                    |
| Up to 2.5 m                     | 8025 CR5                    | 3300 mm single piece | 3140 mm                   | 3250 mm                    |
| From 2.5 - 3.5 m                | 840 CR5                     | 1000 mm extension    | 4140 mm                   | 4250 mm                    |
| 2.3 m TILT Door                 | 820 CR5                     | 2000 mm single piece | 1840 mm                   | 1950 mm                    |


**NOTE:** The Ceiling Fixing Point (Standard) is the position of the hanging bracket measured back from the lintel (see item 1 to 7 of “completed installation”). Also allow 400 mm back from the fixing point for installation of the powerhead (item 7 to 9 of “completed installation”).

The Alternate Fixing Point will position the hanging bracket between the C-Rail brackets, and may line up with a structural support more favourably.




# INTRODUCTION

## 4 TOOLS REQUIRED




## 5 HARDWARE PROVIDED



1. Clevis pin 80 mm (**Section 12**)
2. R clip (**Section 12**)
3. Hexagonal head screw (**Sections 14 & 16**)
4. Nut M8 (**Sections 14 & 16**)
5. Flat washer M8 (**Sections 14 & 16**)
6. Clevis Pin (**Section 16**)
7. R clip (**Section 16**)
8. Screw ST6 x 50 mm (**Section 11 & 14**)
9. Screw ST6,3 x 18 mm (**Sections 9 & 15**)
10. Wallplug 8mm (**Section 11 & 14**)

## 6 COMPLETED INSTALLATION

As you proceed with the assembly, installation and adjustment procedures in this manual, you may find it helpful to refer back to this illustration of a completed installation.



- |                    |                                 |
|--------------------|---------------------------------|
| 1. Header bracket  | 8. Opener                       |
| 2. Belt            | 9. Manual release rope & handle |
| 3. Rail            | 10. Straight door arm           |
| 4. Trolley         | 11. Curved door arm             |
| 5. Rail bracket    | 12. Door bracket                |
| 6. Hanging bracket | 13. C-Rail brackets             |
| 7. Power cord      | 14. Centre rail bracket         |


# INTRODUCTION

## 7 CONTROL PANEL (LOCATED UNDER THE COVER AT THE REAR OF THE OPENER)

1. **External Accessory Power:** 30 Vdc 50 mA available for universal receiver.
2. **Terminal Block:** used for external accessories (see chart below).

| REF | FUNCTION      | COLOUR | POLARITY | COMMENT                                                                 |
|-----|---------------|--------|----------|-------------------------------------------------------------------------|
| 0   | E-Serial port | Green  | +ve      | Serial Communication Input                                              |
| 1   | Push button   | Red    | +ve      | Dry Contact input for push button wired wall controls                   |
| 2   | Ground        | White  | -ve      | Common terminal push button                                             |
| 2   | Ground        | White  | -ve      | Common terminal for The Protector System™ (IR Beams)                    |
| 3   | IR Sensor     | Grey   | +ve      | Chamberlain IR Beam The Protector System™ (pulsing type only)           |
| 4   | Door-in-door  | Green  | +ve      | For Door-in-door dry contact sensor: (see note below)                   |
| 5   | Door-in-door  | Green  | -ve      | Common terminal for Door-in-door dry sensor (4 & 5 are normally linked) |
| 6   | Flasher       | Black  | +ve      | Flashing light output: (24 Vdc 150 mA) while door is in motion          |
| 7   | Flasher       | White  | -ve      | Flashing light output: negative terminal                                |

3. **UP Button:** used for initial programming, to drive the door UP, and for displaying Diagnostic Code - Digit 1.
4. **PROG Button:** used to program door limits, and other features.
5. **DOWN Button:** used for initial programming, to drive the door DOWN, and for displaying Diagnostic Code - Digit 2.
6. **LEARN Button:** used to program transmitters and learn the forces manually.
7. **Indicator LED:** used to indicate various programming modes.
8. **Green Button:** used to activate the door when transmitters are not available. Open - Stop - Close via finger access through the hole in the access cover.
9. **2 PIN plug:** used to connect the opener to the Wireless Beams Base Station.



**NOTE: Door in Door Connections 4 & 5** (used where built-in pedestrian doors are installed within a garage door). Terminals 4 & 5 are normally linked. If the link is removed the opener will not operate. Remove the link and install a Safety switch to prevent the opener from activating the garage door when the built-in pedestrian door is open.

Terminals are designed for operating with a dry contact reed switch or similar.


Door safe condition = closed contacts  
 Door unsafe condition = open contacts.

## ASSEMBLY SECTION

### 8 TIGHTEN THE BELT


**Note:** The spring must be able to compress and bounce during operation. Final tensioning can be performed after installation if necessary. Over tightening the belt may overload the system and cause excessive wear.

1. Tension the belt by adjusting the nut (1), on the pulley assembly, clockwise until the spring is engaged.
2. Continue tightening to compress the spring and remove all the slack in the belt. **DO NOT OVERTIGHTEN** but ensure belt is firm.
3. 36-38 mm as indicated in the diagram is normal.



### 9 FASTEN RAIL TO OPENER

1. Slide the RAIL BRACKET (1) onto the powerhead end of the rail (A) around 200 mm.
  2. Position the rail drive spocket (2) over the opener motor shaft (3) and push down to install.
  3. Secure the rail on the opener with two C-Rail brackets (4) and the screws (5).
- Note:** Only use 18mm Screws (item 9 in Hardware Provided - Section 5).



# INSTALLATION



**Wear protective goggles when working overhead to protect your eyes from injury. Disengage all existing garage door locks to avoid damage to the garage door. To avoid serious personal injury from entanglement, remove all ropes connected to the garage door before installing the opener.**


## 10 HEADER BRACKET POSITIONING

The header bracket must be rigidly fastened to a structural support of the garage. Reinforce the wall or ceiling with a 40 mm (1-1/2") board if necessary. Failure to comply may result in improper operation of safety reverse system.

You can attach the header bracket either to the header wall (1) or to the ceiling (3). Follow the instructions which will work best for your particular requirements.

With the door closed, mark the vertical centre line (2) of the garage door. Extend line onto header wall above the door.

Open door to highest point of travel. Draw an intersecting horizontal line (4) on header wall at least 50 mm above high point to provide travel clearance for top edge of door.




## 11 INSTALL THE HEADER BRACKET

**NOTE: Refer to vertical centre and horizontal lines created in the previous section for proper placement of header bracket.**

A. Wall mount: centre the header bracket (1) on the vertical centre line (2) with the bottom edge of the header bracket on the horizontal line (4) (with the arrow pointing toward the ceiling).

Drill and secure the Header Bracket using the most suitable variation of holes (5). If using the wood screws provided (3) (item 8 in the Hardware Provided - Section 5), use a 4.5 mm pilot drill. If securing to a metal fixture, self tapping "tek" screws may be more suitable.

B. Ceiling mount: extend vertical centre line (2) onto the ceiling. Centre the header bracket (1) on the vertical mark no more than 150 mm (6") from the wall. Make sure the arrow is pointing toward the opener. Drill and secure the Header Bracket using the most suitable variation of holes (5). If using the wood screws provided, use a 4.5 mm pilot drill. If securing to a metal fixture, self tapping "tek" screws may be more suitable. For concrete ceiling fixtures, 8 mm wall plugs are provided.




## 12 ATTACH RAIL TO HEADER BRACKET

**Attach the Rail to the Header Bracket**

- Position the assembled opener on the garage floor below the header bracket. Use foam packing material as a protective base.

**NOTE: If the door spring is in the way you'll need help. Have someone hold the opener securely on a temporary support to allow the rail to clear the spring.**

- Position the rail bracket against the header bracket.
- Align the bracket holes and secure with the 80 mm clevis pin and "R" clip (1) item 1 in the Hardware Provided - Section (5) and (2) (item 2 in the Hardware Provided - Section 5).



# INSTALLATION

## 13 POSITION THE OPENER

Disengage the trolley mechanism (see section “Operating the manual release”) and slide it back towards the powerhead. Secure the hanging push arm temporarily to the rail assembly using tape or rope to prevent it from becoming a hazard.

### SECTIONAL DOOR


You will need a 50 mm piece of timber or similar spacer to gauge the distance between door and rail.

1. Raise the opener onto support.
2. Open the door completely, place a 50 mm spacer between the door and the rail (as shown).
3. The final positioning of the rail should be relatively parallel to the horizontal door panels.

### ONE PIECE TILT DOOR

You will need a 50 mm piece of timber or similar spacer to gauge the distance between door and rail.

1. Raise the opener onto support.
2. Open the door completely, place a 50 mm spacer between the door and the rail (as shown).
3. The top of the door should be level with the top of the opener. Do not position the opener more than 50 mm above this point.  
Ensure the opener is not positioned too low as to cause a hazard to vehicles or persons.



# INSTALLATION

## 14 HANG THE OPENER

The opener must be securely fastened to a sound structural support above the opener.

1. Position the opener as in the previous step. Check the rail is centred over the door. Ensure the rail brackets (fig.1) is on the Powerhead end of the rail in a position as close to the opener as possible (X).
2. If mounting directly onto the ceiling, (fig.2) screw the bracket directly into a structural support on the ceiling.
3. If hanging the opener below the ceiling, (fig.3) bend the hanging brackets provided, and secure to both the ceiling and the rail bracket.
4. Check the opener is securely centred over the door. Remove the 50 mm spacer, and any other assembly tools. Operate the door manually and check for unrestricted operation.

fig.1










fig.2



Item 8 in Hardware  
Provided - Section 5

Item 10 in Hardware  
Provided - Section 5

fig.3



Item 3 in Hardware  
Provided - Section 5

Item 4 in Hardware  
Provided - Section 5

Item 8 in Hardware  
Provided - Section 5

Item 10 in Hardware  
Provided - Section 5


## 15 FASTEN DOOR TO BRACKET

The door bracket must be securely fastened to the frame or a structural support on the door.

### Mounting position for Sectional Doors

1. Align the bracket on the centre line, measure down 100-300 mm from the door top edge.
2. Secure the bracket in this position, using the most suitable variation of holes available.

A



# INSTALLATION




## 16 ATTACH DOOR ARM TO TROLLEY

Make sure the garage door is fully closed. Pull the manual release cord to disengage the trolley. Slide the trolley to around 300 mm from the header bracket.

1. The straight door arm is already preassembled to the trolley.
2. Install the curved arm onto the door bracket using the Clevis pin (2) (*item 6 in the Hardware Provided - Section 5*) and R-Clip. (3) (*item 7 in the Hardware Provided - Section 5*) supplied.
3. Move the straight and curved arms together and secure using two bolts and nuts provided (4) (*items 3 & 4 in the Hardware Provided - Section 5*).

For optimal performance, ensure the straight arm is positioned at approximately 20° from vertical when the door is fully closed.

**Alternate Arm Configuration:** The curved arm can be assembled directly to the trolley assembly if required (see fig.3). Unscrew the front two screws in the trolley assembly. Remove the straight arm pivot and reassemble with the curved arm bracket.



## 17 OPERATING THE MANUAL RELEASE



**DO NOT DISENGAGE THE OPENER TO MANUAL OPERATION WITH CHILDREN, PERSONS OR OTHER OBJECTS INCLUDING MOTOR VEHICLES WITHIN THE DOORWAY:** (The door is under significant tension and if the door has developed a fault or incorrect tension, it may be unsafe and may fall rapidly).

The manual release mechanism enables the door to be manually operated during power outages or in an emergency.

The RED Manual Release cord is preassembled to the trolley. When the opener is installed the handle should be no higher than 1.8 metres from the floor. The cord may need to be extended.



Attach the manual release Instruction Label to the cord as indicated in fig 1.

**DO NOT USE THE RED HANDLE TO OPEN AND CLOSE THE DOOR.**

**To operate the Manual Release:**

The door should be fully closed if possible.

1. **Disengage:** Pull the manual release rope and handle down once to disconnect. This will disengage the trolley, allowing the door to be moved by hand, UP and DOWN as many times as needed.
2. **Re-engage:** Press the "GREEN" button in the centre of the trolley assembly. This will re-engage the trolley, and when the door passes the trolley position it will automatically re-engage the opener.



**Connect Electric Power**


**TO AVOID INSTALLATION DIFFICULTIES, DO NOT RUN THE GARAGE DOOR OPENER UNTIL INSTRUCTED TO DO SO. Connect to properly fused and earthed power outlet.**

- Ensure all ropes and installation tools have been removed from the door.
- When the opener is switched ON, the operator light flashes a number of times and then remains ON.



## 18 PROGRAM THE TRAVEL LIMITS AND FORCE SETTINGS

Travel limits regulate the points at which the door will stop when moving UP or DOWN. The travel limit buttons are located under the access cover on the rear panel (fig.1).



**NOTE:** This opener uses a **POSITION TAB** attached to the belt which activates a mechanical passpoint during the door travel. The indicator LED will blink when this occurs. If the passpoint is not activated during the door travel process, the travel limits cannot be programmed.

1. Ensure the door is engaged to the opener trolley before setting the limits, otherwise the trolley may move independently and jam into the powerhead assembly. Press the **PROG** Button until the **UP** Arrow Button begin to flash (fig.2).
2. Press and hold the **UP** Arrow Button until the door is in the desired UP position (fig.3).

**NOTE:** The **UP** and **DOWN** Arrow Buttons can be used to move the door up and down as needed.

3. Once the door is in the desired UP position press and release the **PROG** Button. The **DOWN** Arrow Button will begin to flash (fig.4).
4. Press and hold the **DOWN** Arrow Button until the door is in the desired DOWN position (fig.5).

**NOTE:** The **UP** and **DOWN** Arrow Buttons can be used to move the door up and down as needed.

5. Once the door is in the desired DOWN position press and release the **PROG** Button. The indicator LED and the **UP** arrow will flash quickly (fig.2).

### SETTING THE FORCE (AUTO):

6. Press and release the **UP** Arrow Button to test the UP limit. When the door has travelled to the programmed UP limit, the **DOWN** Arrow Button will begin to flash.
7. Press and release the **DOWN** Arrow Button to test the DOWN limit. The door will travel to the programmed DOWN limit. The indicator LED will stop flashing. The travel limits and force setting has now been set. Proceed to test safety reverse system.

### SETTING THE FORCE (MANUAL LEARN IF REQUIRED):

1. Start with the door fully CLOSED.
2. Open the rear access panel. Locate the yellow Learn button.
3. Push the yellow Learn button twice to enter Force Adjustment mode. The indicator LED and the UP arrow will flash quickly.
4. Press and release the UP Arrow Button. The door will travel to the programmed UP Limit.
5. The indicator LED and the DOWN arrow will flash quickly.
6. Press and release the DOWN Arrow Button. The door will travel to the programmed DOWN limit.

The Indicator LED will stop flashing when the force has been set. The door must travel through a complete cycle, UP and DOWN, in order for the force to be set properly. If the unit cannot open and close your door fully, inspect your door to insure that it is not sticking or binding.



*Without a properly installed safety reversal system, persons (particularly small children) could be **SERIOUSLY INJURED** or **KILLED** by a closing door.*

- *Incorrect adjustment of garage door travel limits will interfere with proper operation of safety reversal system.*
- ***NEVER** use force adjustments to compensate for a binding or sticking garage door.*
- *After **ANY** adjustments are made, the safety reversal system **MUST** be tested. Door **MUST** reverse on contact with 40 mm high object laid flat on floor.*

## CAUTION

To prevent damage to vehicles, be sure fully open door provides adequate clearance.

fig.2




fig.3




fig.4





fig.5



## ADJUSTMENT SECTION


### 19 TEST THE SAFETY REVERSE SYSTEM



**The safety reverse system test is important. Garage door must reverse on contact with a 40 mm obstacle laid flat on the floor. Failure to properly adjust opener may result in serious personal injury from a closing garage door. Repeat test once a month and adjust as needed.**

**Procedure:** With door opened place a 40 mm obstacle (1) laid flat on the floor under the garage door. Operate the door in the down direction. The door must reverse off the obstacle. If the door stops on the obstacle, remove obstacle and repeat Program the Limits and Force Steps, then repeat safety reverse test.

When the door reverses off the 40 mm obstacle, remove the obstacle and run the opener through a complete travel cycle. Door must not reverse in closed position. If it does, repeat Program the Limits and Force then repeat safety reverse test.



### 20 PROGRAM THE TRAVEL SPEED (OPTIONAL)

**TRAVEL SPEED:** Automatically selected:

There are two travel speeds available for this opener.

The speed is a function of door travel distance and is automatically set during the door travel limit setting process.

- Travel distance longer than 1.6 metres = REGULAR speed
- Travel distance shorter than 1.6 metres = SLOW speed (will suit tilt doors best.)

**TRAVEL SPEED:** Manually selected:

The speed can be set manually if required, once the travel limits have been set, using the following method.

To activate the alternate speed:

PRESS and HOLD both the UP and DOWN arrows for 3 seconds. The courtesy lamp will flash once to confirm SLOW speed and twice to confirm REGULAR speed.

To deactivate the selected speed: Repeat the process above (toggle between the two settings).

### 21 THE PROTECTOR SYSTEM™ (IR BEAMS) (OPTIONAL)

**NOTE:** This accessory must be used for all installations where the closing force as measured on the bottom of the door is over 400 N (40 kgf).

**SPECIAL NOTE:** Merlin strongly recommends that The Protector System™ (IR Beams) be installed on all garage door openers.

**IR BEAMS:** By installing IR Beams, an open door is prevented from closing if a person or object is located in the beam area. If the door is already closing, it will return to the open position. A closed door is not prevented from opening.

If the Protector System™ (IR Beams) is installed and needs to be removed, the opener will need to be reprogrammed (refer to paragraph 4 of the troubleshooting section).



**To prevent entrapment, install The Protector System™ (IR Beams) no higher than 100 mm above the floor.**

**Disconnect power to the garage door opener before installing The Protector System™ (IR Beams)**

#### SAFETY FIRST!



Whilst Merlin have engineered safety features into your garage door opener, we urge you to consider fitting The Protector System™ (IR Beams) to your new garage door opener. In many countries these devices are compulsory to assist in preventing serious injury or property damage. For your own peace of mind and the safety of others please install this inexpensive safety device.

# PROGRAMMING

## 22 PROGRAM TRANSMITTERS TO THE OPENER LIGHT

**NOTE: Do not use the same transmitter button that has been previously learned to the garage door opener for operation.**

To Program your transmitters to operate your garage door opener light follow the below steps:



1. Press and release the "LEARN" button, and the the indicator LED will stay ON (fig.1).
2. Press and release the "PROG" button and the garage door opener will go into courtesy light learn mode for 30 seconds (fig.2).
3. Press any transmitter button (fig.3) to learn this button to the garage door opener courtesy light, the garage door opener "courtesy light" will flash twice.

The transmitter is now learnt to the garage door opener courtesy light.

### To Erase all Transmitter Codes

1. Press and hold the LEARN button on the operator, the indicator LED will turn ON, continue to hold the LEARN button for approximately 8 seconds, until the indicator LED turns OFF.
2. Release the button, all codes are now erased.

**NOTE: Erasing all transmitter codes, as in the Wireless programming section, will also delete this feature.**



## 23 ADJUSTABLE COURTESY LIGHT TIME CHANGE

This feature will allow you to adjust the garage door opener light "ON" time as desired. The courtesy light "ON" time is factory default set to 3 minutes.






**NOTE: Every time you enter into program mode the unit will start at the default time of 3 minutes.**

1. Press and release the "LEARN" button (fig.1), and the indicator LED will turn on solid.
2. Press and release the "PROG" button twice (fig. 2). The courtesy light will flash once. The garage door opener is now in courtesy light "time selection mode" for 30 seconds\*.
3. Press the "UP" arrow button (fig. 3) to increase the courtesy light "ON" time:
  - 1 press of the "UP" arrow button will change the courtesy light "ON" to 5 minutes.
  - 2 presses of the "UP" arrow button will change the courtesy light "ON" time to 10 minutes.
4. Press the "DOWN" arrow button (fig.4) to decrease the courtesy light "ON" time:
  - 1 press of the "DOWN" arrow button will change the courtesy light "ON" to 1.5 minutes.
  - 2 presses of the "DOWN" arrow button will change the courtesy light "ON" time to 30 seconds.

**NOTE: The courtesy light will flash once each time the "UP" or "DOWN" arrow button is pressed.**

5. Press "PROG" button (fig.5) on the opener to save the settings. The courtesy light flashes twice.

**\* NOTE: If after 30 seconds no button is pressed, the garage door opener will exit from program mode and the courtesy light will flash 5 times. No settings will have been saved.**



## 24 TIMER TO CLOSE FEATURE (TTC)



*Door may operate unexpectedly, therefore do not allow anything to stay in the path of the door.*

The Timer to Close feature requires The Protector System™ (IR Beams) (Accessory - WBKIT-M or 772ANZ) to be installed.

### Operation:

This feature allows the door to automatically close from a fully open position after a specified time. The delay can be set from 10 to 180 seconds in 10 second increments, by using the opener control buttons.

If the door encounters an obstruction while closing, the door will stop and return to the UP position. The Courtesy lamp will then flash 10 times.





### To Activate TTC, or change a preset time:

1. Start with the door fully **CLOSED** (fig.1).
2. Enter into TTC Activation mode by pressing both **PROG** and **DOWN** buttons together for 3 seconds (fig.2). Release when the courtesy light flashes twice.
3. Press the **UP** button once for each 10 second increment required of TTC (fig.3. eg. twice for 20 seconds). Press the **DOWN** arrow to reduce, if needed.
4. Press and release the **PROG** button to save this time (fig.4), courtesy light will flash once. TTC is now activated.

**TEST:** Operate the door to the UP position. Keep clear of the IR Beams and check the door closes after the preset time.

### To Deactivate TTC:

1. Enter into TTC Activation mode by pressing both **PROG** and **DOWN** buttons together for 3 seconds (fig.2). Release when the courtesy light flashes twice.
2. Press and release the **PROG** button to save (fig.4), courtesy light will flash once. TTC is now deactivated.



## 25 INSTALLING YOUR E148M FOUR BUTTON WIRELESS WALL MOUNT REMOTE CONTROL

**NOTE:** The wall control supplied with your opener is pre-programmed by the factory.

If adding a new wall control, program into the opener before mounting the unit as detailed in Wireless Programming.





*Disconnect power to the opener before installing this accessory to prevent accidental activation. Locate minimum 1.5 m above the floor.*


### To install:

- Carefully pry open (fig.1) the E148M and locate the two screws for mounting.
- Attach to the wall using the two screws (fig.2) and wall anchors provided if mounting to a plaster wall. If using a recessed wall box do not use anchors.

**NOTE:** Do not overtighten screws.



## 26 INSTALL WARNING LABELS



Three warning labels are provided with this opener: attach as indicated above to a clean and suitable surface.

1. Warning and Risk of entrapment: Place on the inside of the door (1).
2. EMERGENCY Release/Service label: - place on the Manual Release cord (2).

## 27 PARTIAL OPENING FEATURE (PET)

**NOTE:** Do not use the same transmitter button that has been previously learned to the garage door opener for operation.

This is an adjustable, mid stop position suitable for ventilation, pedestrian or pet access, programmed to the transmitter.

**To Activate this feature:**


1. Start with the door fully **CLOSED** (fig.1). Drive the opener **UP** (fig.2) and stop at the position required for **PET** access.
2. Enter PET activation mode by pressing the **PROG** and **UP** buttons together for 3 seconds (fig.3). Release when the courtesy light flashes once.
3. Press the transmitter button that you have allocated for this feature (fig.4). Do not use the button already allocated for normal operation. The courtesy light will flash once when the code is accepted.

**TEST:** Press the transmitter once, and door will close, press again, and door will return to the preset position. If the door is above the preset position, when the button is pressed, it will fully close.

**To Deactivate this feature:**

1. Start with the door fully **CLOSED**.
2. Enter PET deactivation mode by pressing the **PROG** and **UP** buttons together for 3 seconds (fig.3). The courtesy light will flash twice, indicating the deactivation has occurred.

**NOTE:** Erasing all transmitter codes, as in the Wireless programming section, will also delete this feature.



# WIRELESS PROGRAMMING

## 28 WIRELESS PROGRAMMING (OPTIONAL ACCESSORIES)



*Activate the opener only when door is in full view, free of obstruction and properly adjusted. No one should enter or leave garage while door is in motion. Do not allow children to operate push button(s) or transmitter(s). Do not allow children to play near the door.*

**NOTE:** The transmitter(s) and wireless wall button supplied with your opener are preprogrammed by the factory.

If you purchase additional transmitters, the garage door opener must be programmed to accept the new transmitter code.


### Programming Transmitters:

1. Press and Hold the button on the hand-held transmitter that you wish to use (1).
2. Press and release the yellow “LEARN” button on the opener (2).
3. Release the transmitter button when the opener light flashes. It has learnt the code. If you release the transmitter button before the opener light flashes, the opener has not learned the code.

Now the opener will operate when the transmitter button is pressed.

### To Erase all Transmitter Codes:

1. Press and Hold the yellow “LEARN” button on the opener until the indicator LED goes ON, and continue holding for approx. 6 seconds, until the indicator LED goes out.
2. Release the button, all codes are now erased.





# MAINTENANCE AND CARE OF YOUR OPENER

## 29 USING YOUR OPENER

### Automatic Operation

Your opener can be activated by any of the following devices:

- Opener control panel: UP and DOWN Buttons and Green Push Button.
- An Outside Keyswitch (760E)
- Wireless Security Keypad
- A transmitter: Press and hold the programmed button until the door starts to move.

When the opener is activated by transmitter:

- If open, the door will close.
- If closed, the door will open.
- If closing, the door will stop.
- If opening, the door will stop (allowing space for entry and exit of pets and for fresh air).
- If the door has been stopped in a partially open or closed position, it will reverse direction.
- If an obstruction is encountered while closing, the door will reverse to the UP limit.
- If an obstruction is encountered while opening, the door will stop and briefly reverse.
- The IR Beams uses an invisible beam which, when obstructed, causes a closing door to open and prevents an open door from closing. It is **STRONGLY RECOMMENDED** for homeowners with young children.

### Manual Operation

- Door should be fully closed if possible. Weak or broken springs could allow an open door to fall rapidly. Property damage or serious personal injury could result.
- **To Disengage:** Pull the manual release rope and handle down once to disconnect. This will disengage the trolley, allowing the door to be moved by hand, UP and DOWN as many times as needed.
- **To Re-engage:** Pull the manual release rope towards the motor until it springs back to its original horizontal position. This will prepare the trolley to engage with the trolley latch. Activate the opener using the control panel or transmitter. This will automatically re-engage the door to the opener.
- Do not use the manual release handle to pull the door open or closed.

### Courtesy Light

The opener lights will turn on under the following conditions:

- When the opener is initially plugged in.
- When power is restored after interruption or when the opener is activated.
- Lights will turn off automatically after 3 minutes or as per the programmed courtesy light duration (See Adjustable Courtesy Light Time Change - Section 23).

## 30 CARE OF YOUR OPENER

### Once a Month

- Manually operate door. If it is unbalanced or binding, call a qualified door technician.
- Check to be sure door opens & closes fully.
- Adjust limits and/or force if necessary.
- Repeat the safety reverse test. Make any necessary adjustments.

### Once a Year

- Using a multipurpose grease, lightly grease the belt and inside the rail assembly where the trolley slides.
- Internally the opener does not require additional lubrication.

## 31 REPLACE BATTERIES IN TRANSMITTERS

### Battery of the transmitter:

The batteries in the transmitter have an extremely long life. If the transmission range decreases, the batteries must be replaced. Batteries are not covered by the warranty.



**WARNING! The wireless transmitters contain button/coin cell batteries.**

- **The battery is hazardous.**
- **Keep new and used batteries away from children.**
- **Do not ingest battery. Chemical burn hazard.**
- **If the coin cell battery is swallowed or placed inside any part of the body, it can cause severe or fatal injuries in 2 hours or less.**




- **If the battery compartment does not close securely, stop using the product and keep away from children.**
- **If you think batteries might have been swallowed or placed inside any part of the body, call the 24-hour Poisons Information Centre on 13 11 26 in Australia, or the 24-hour National Poisons Centre on 0800 764 766 in New Zealand, or seek immediate medical attention.**
- **Dispose of used coin/button cell batteries immediately and safely. Flat batteries can still be dangerous.**

### Replacing battery (CR2032):


E970M, E975M, E980M, E985M, E964M & E960M:

Turn the transmitter over and open the case using a small Phillips-head screwdriver. Lift/slide off the rear cover and carefully remove the circuit board. Observing the polarity, take out the old battery. Insert the new battery into the holder, ensuring the polarity is correct. Reassemble the transmitter in reverse order.



E148M, E943M, E940M & E945M:

Use a flat-blade screwdriver to gently pry open the case as shown below. Observing the correct polarity, remove the old battery. Insert the new battery, ensuring the polarity is correct. Clip the case back together.






# ACCESSORIES


## 32 ACCESSORIES

- |                |                                |                     |                             |
|----------------|--------------------------------|---------------------|-----------------------------|
| 1. Model E148M | 4 Channel wireless wall button | 7. Model 774ANZ     | The Protector System™       |
| 2. Model E975M | 4 Channel transmitter          | 8. Model E1702M     | Key Operated Manual Release |
| 3. Model E985M | 4 Channel transmitter          | 9. Model 760E       | Outside keyswitch           |
| 4. Model E964M | 4 Channel visor transmitter    | 10. Model 837AU myQ | Remote LED Light            |
| 5. Model E960M | 4 Channel transmitter          | 11. Model M-BBU24V  | Battery Backup              |
| 6. Model E840M | Wireless Security Keypad       | 12. WBKIT-M         | Wireless Safety Beams Kit   |



NOTE: Use of any Chamberlain Group accessories are approved to use with this opener. This includes genuine Merlin accessories. Generic compatible accessories are NOT approved for use with this opener.

## 33 RAIL HARDWARE




# REPLACEMENT PARTS

## 34 REPLACEMENT PARTS



If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid hazard.




### RAIL REPLACEMENT PARTS



041A4017-1  
Motor shaft adapter



041A4016R  
Position tab (belt)



041A4021R  
Trolley latch (belt)

## 35 TROUBLESHOOTING

### 1. Opener doesn't operate from either door control or transmitter:

- Does the opener have electric power? Plug lamp into outlet. If it doesn't light, check the fuse box or the circuit breaker. (Some outlets are controlled by a wall switch.)
- Have you disengaged all door locks? Review installation instruction warnings on page 2.
- Is there a build-up of ice or snow under door? The door may be frozen to ground. Remove any obstruction.
- The garage door spring may be broken. Have it replaced.

### 2. Door operates from door control but not from transmitter:

- Replace batteries in the transmitter if necessary.
- If you have two or more transmitters and only one operates, review Program Your Opener, Transmitter and Keyless Entry.

### 3. Transmitter has short range:

- Check the battery in the transmitter is fully charged.
- Change the location of the transmitter in the car.
- A metal garage door, foil-backed insulation or metal siding will reduce the transmission range.

### 4. Door reverses for no apparent reason and opener light flashes 10 times:

Check The Protector System™ (IR Beams) (if you have installed this accessory). If the light is flashing, correct alignment.

If the Protector System™ (IR Beams) is installed and needs to be removed, the Opener will need to be reprogrammed as follows:

- Remove the IR Beam wiring from the Opener.
- Turn the power OFF for 5 seconds.
- Turn the power ON for 5 seconds.
- Again turn the power OFF for 5 seconds.
- Turn the power back on and test the opener for normal operation.

### 5. The garage door opens and closes by itself:

Make sure transmitter button is not stuck "on".

### 6. Door stops but doesn't close completely:

Repeat Programming the Travel Limits.

Repeat safety reverse test after any adjustment of door arm length, close force or down limit adjustments.

### 7. Door opens but won't close:

- Check The Protector System™ (IR Beams) (if you have installed this accessory). If the light on The Protector System™ (IR Beams) are flashing, correct the alignment.
- If opener light does not flash and it is a new installation, repeat Programming the Travel Limits.

Repeat the safety reverse test after the adjustment is complete.

### 8. Opener strains:

Door may be unbalanced or springs are broken. Close door and use manual release rope and handle to disconnect trolley. Open and close door manually. A properly balanced door will stay in any point of travel while being supported entirely by its springs. If it does not, call for professional garage door service to correct the problem.

### 9. Opener hums briefly, then won't work:

- Garage door springs are broken. SEE ABOVE.
- If problem occurs on first operation of opener, door is locked. Disable door lock.

Repeat safety reverse test after adjustment is complete.

### 10. Opener won't activate due to power failure:

- Pull manual release rope and handle down once to disconnect trolley. Door can be opened and closed manually. When the power is restored, press the "GREEN" button in the centre of the trolley assembly. The next time the opener is activated, the trolley will re-connect.
- The Outside Quick Release accessory (if fitted) disconnects the trolley from outside the garage in case of power failure.

### 11. The opener runs, but the carriage does not move:

- Check the carriage is not disengaged from the opener. Operate the manual release to re-engage the opener.
- In a new installation, the preassembled Motor Shaft Adapter may have fallen out of the belt sprocket assembly. This adapter is installed during the manufacturing process and may have dislodged.
- In older installations, especially on excessively heavy doors, check the Motor Shaft Adapter has not stripped.

### 12. The Up and DOWN arrows on the control panel are flashing in sequence:

Check the diagnostic code on next page.

# DIAGNOSTICS

## 36 DIAGNOSTIC CHART

Your garage door opener is programmed with self-diagnostic capabilities. The UP and DOWN arrows on the garage opener flash the diagnostic codes.

| DIAGNOSTIC CODE       |                         | SYMPTOM                                                                                          | POSSIBLE RESOLUTION                                                                                                                                                                                                                                                                                               |
|-----------------------|-------------------------|--------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UP Arrow<br>Flash(es) | DOWN Arrow<br>Flash(es) |                                                                                                  |                                                                                                                                                                                                                                                                                                                   |
| 1                     | 1                       | The garage door opener will not close and the courtesy light flashes.                            | The Protector System™ (IR Beams) has lost connection with the garage door opener. Please check the beam connection and alignment for wireless installations or inspect for damaged or cut wires in wired installations.                                                                                           |
| 1                     | 2                       | The garage door opener will not close and the courtesy light flashes.                            | There is a short or reversed wire for the The Protector System™ (IR Beams). Inspect safety sensor wire at all staple points and connection points and replace wire or correct as needed.                                                                                                                          |
| 1                     | 3                       | The door control will not function.                                                              | The wires for the door control are shorted or the door control is faulty. Inspect the wire at all staple points and connection points and replace wire or correct as needed.                                                                                                                                      |
| 1                     | 4                       | The garage door opener will not close and the courtesy light flashes.                            | The Protector System™ (IR Beams) are misaligned or were momentarily obstructed. Realign both sensors to ensure both LEDs are steady and not flickering. Make sure nothing is hanging or mounted on the door that would interrupt the sensors path while closing.                                                  |
| 1                     | 5                       | There is no door movement or motor accelerates before stopping suddenly.                         | No RPM pulses have been detected. Check the door manually for balance, binding or obstructions. Internally the possible cause may be the motor, logic board or RPM sensor. Try resetting door travel limits. Contact service centre.                                                                              |
| 1                     | 6                       | Door continues to move after the motor stops.                                                    | RPM pulses have been detected after motor has turned off. Possible broken spring. Check the door is correctly balanced and not creeping up or down. Contact a door service centre.                                                                                                                                |
| 2                     | 1-5                     | Opener fails to operate.                                                                         | Possible logic board failure. Reboot opener by turning the mains power OFF and then ON after 15 seconds. Reprogram the door travel limits and force settings. Contact service centre.                                                                                                                             |
| 2                     | 6                       | Unable to set travel limit down direction. Passpoint has not been recognised during programming. | Check the passpoint module has been activated by the chain Position Tab, during the door travel. Reset the travel limits.                                                                                                                                                                                         |
| 3                     | 2                       | Unable to set the travel or retain position.                                                     | Check travel module for proper assembly, replace if necessary.                                                                                                                                                                                                                                                    |
| 3                     | 3                       | The battery status LED* is constantly flashing green.                                            | Battery backup charging circuit error, replace logic board *(if applicable).                                                                                                                                                                                                                                      |
| 4                     | 1-4                     | Door is moving, stops and or reverses.                                                           | Manually open and close the door. Check for binding or obstructions, such as a broken spring or door lock. If the door is binding or sticking contact a trained door systems technician. If door is not binding or sticking attempt to reprogram travel (refer to "Program the Travel Limits and Force" section). |
| 4                     | 5                       | Opener runs approximately 150 mm to 200 mm, stops and reverses.                                  | Communication error to travel module. Check travel module connections, replace module if necessary.                                                                                                                                                                                                               |
| 5                     | 1-4                     | Door fails to operate or operates erratically. External accessory wiring failure.                | Check the external wiring to the control panel terminal is wired correctly. Turn off power, remove all external wiring, and retest door operation.                                                                                                                                                                |
| 5                     | 5                       | Door opener fails to operate.                                                                    | Low internal voltage on the logic board, possible power transformer or logic board failure. Service required, call a trained service specialist.                                                                                                                                                                  |

# SPECIFICATIONS

## 37 SPECIFICATIONS - COMMANDER ELITE II - MS107MYQ

|                                         |                                                                                                                 |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Input Voltage. . . . .                  | 220-240 Vac, 50 - 60 Hz                                                                                         |
| Max. Pull Force. . . . .                | 1000 N                                                                                                          |
| Power. . . . .                          | 225 Watt                                                                                                        |
| Normal Torque. . . . .                  | 7 Nm                                                                                                            |
| Max. door weight. . . . .               | 150 kg                                                                                                          |
| Max. lift under spring tension. . . . . | 20 kg                                                                                                           |
| Max. door area. . . . .                 | Sectional doors and Tilt doors 20.0m <sup>2</sup>                                                               |
| <b>Motor</b>                            |                                                                                                                 |
| Type. . . . .                           | DC gearmotor permanent lubrication                                                                              |
| Noise level. . . . .                    | 54 db at 1 metre                                                                                                |
| <b>Drive Mechanism</b>                  |                                                                                                                 |
| Drive. . . . .                          | Belt with one-piece trolley on steel rail                                                                       |
| Length of Travel. . . . .               | Adjustable to 3.0 m                                                                                             |
| LED light. . . . .                      | 25 Watt equivalent                                                                                              |
| Door Linkage. . . . .                   | Adjustable door arm. Pull cord trolley release                                                                  |
| <b>Safety</b>                           |                                                                                                                 |
| Personal. . . . .                       | Push button stop in <b>UP and DOWN</b> direction. Automatic safety reverse in both <b>UP and DOWN</b> direction |
| Electronic. . . . .                     | Automatic force adjustment                                                                                      |
| Electrical. . . . .                     | Transformer overload protector and low voltage push button wiring                                               |
| Limit Device. . . . .                   | Mechanical Passpoint/RPM sensor                                                                                 |
| Limit Adjustment. . . . .               | Electronic                                                                                                      |
| Soft-start/Soft-stop                    |                                                                                                                 |
| <b>Dimensions</b>                       |                                                                                                                 |
| Length (Overall). . . . .               | 3.24 m                                                                                                          |
| Headroom Required. . . . .              | 30 mm                                                                                                           |
| Hanging Weight. . . . .                 | 12 kg                                                                                                           |
| <b>Receiver</b>                         |                                                                                                                 |
| Memory Registers. . . . .               |                                                                                                                 |
| Operating Frequency. . . . .            | 64 handset codes. 4 keypad devices - 1 code each<br>433.30/433.92/434.54 MHz                                    |

## Warranty Registration

To validate your warranty you must complete the registration form online at:




[gomerlin.com.au/warranty](http://gomerlin.com.au/warranty) OR [gomerlin.co.nz/warranty](http://gomerlin.co.nz/warranty)

**Merlin**  
POWERING GARAGE  
DOORS & GATES

## Get Connected with myQ

Additional purchase of the myQ Connectivity Kit is required to enable myQ functionality.



Visit [www.gomerlin.com.au](http://www.gomerlin.com.au) or [www.gomerlin.co.nz](http://www.gomerlin.co.nz) for more details.



™ Trademark of The Chamberlain Group LLC

® Registered Trademark of The Chamberlain Group LLC

© 2026 The Chamberlain Group LLC

## Limited Warranty in Australia and New Zealand

### Merlin® Commander Elite II MS107MYQ

#### Garage Sectional and Tilt Door Opener

#### 1 Your consumer rights and guarantees

This Limited Warranty is provided by Chamberlain Australia Pty Ltd, Chamberlain New Zealand Limited (**Chamberlain**), contact details in Section 5 below. This Limited Warranty applies to the Merlin® Commander Elite II MS107MYQ unit (Unit) purchased in Australia and New Zealand, and gives you benefits which are in addition to your consumer rights and remedies under the Australian Consumer Law (or corresponding New Zealand consumer protection laws).

You can find out more information about your consumer rights and guarantees which the law provides in Australia at [www.accc.gov.au](http://www.accc.gov.au), in New Zealand at [www.consumerprotection.govt.nz](http://www.consumerprotection.govt.nz). We also provide this statement as required under the Australian Consumer Law:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

#### 2 What does our Limited Warranty cover?

Chamberlain warrants that, when purchased new in Australia or New Zealand, the Unit (all parts of the Unit other than globes and batteries) is free from defects in materials and workmanship (Limited Warranty) for the Limited Warranty period, subject to the terms and conditions of this Limited Warranty.

The Limited Warranty period (for Accessories see below) is 7 years (84 months) or 15,000 cycles (each opening and closing of the garage door equals 1 cycle) whichever comes first, from the date of purchase of the Unit when installed by a Professional Dealer authorised by Chamberlain in residential premises with a residential specified garage door that is designed for the sole purpose of a single-family dwelling.

The Limited Warranty period for remote controlled transmitters and accessories included with the Unit (Accessories) is 12 months from the date of purchase.

#### 3 Limited Warranty Conditions

The following terms and conditions apply to your Limited Warranty:

- our Limited Warranty is effective from date of purchase as indicated in Section 2 above;
- proof of purchase of the Unit is required;
- purchaser must ensure the garage door is serviced by a Chamberlain authorised dealer or qualified technician during the period 24 to 36 months and 60 to 72 months after the date of purchase. If your door binds, sticks, or is out of balance, then it must not be used until serviced by a Chamberlain authorised dealer or qualified technician. The garage door service fee will be at the purchaser's expense.

Please also see the User Manual for the Unit available on our website.

#### 4 What is not covered

- Batteries and globes are not covered under the Chamberlain Limited Warranty.
- Travel costs incurred by Chamberlain or its authorised dealer in either travelling to and from areas outside a capital city area. These costs will be at the purchaser's expense.
- Additional access costs incurred by Chamberlain or its authorised dealer in obtaining access to premises where the Unit is not readily accessible. These costs will be at the purchaser's expense.

Our Limited Warranty covers defects as explained, and does not cover all problems and mishaps that may occur in relation to the Unit including:

- when the unit is not installed within outlined specification for that unit or as outlined within the user manual;
- you got what you asked for but simply changed your mind, found it cheaper somewhere else, decided you did not like the purchase or had no use for it;
- you misused the Unit in any way that caused the problem;
- you knew of or were made aware of any deficiencies with the Unit before date of purchase;
- use of the Unit with controls or third party devices or software which has not been supplied, or pre-approved, by Chamberlain;
- problems relating to or residing in third party hardware, software or other items with which our product is used;

- any loss of data related to you or provided by you, or loss related to downtime associated with use of the product, whether through power outage, failure of internet or wireless connectivity, network disruptions, or otherwise;
- non-compliance with the relevant instructions in the User Manual;
- tampering, neglect, abuse, wear and tear, accident, electrical storm, excessive use or conditions other than normal use;
- problems with, or relating to, the garage door or garage door hardware, including but not limited to the door springs, door rollers, door alignment, hinges, guides, slats and drums;
- problems caused by electrical faults or replacement of batteries or light bulbs, blown fuses, electrical surges, power surges or power strikes, fire, flood, rain, water, lightning or storms;
- water or moisture ingress that causes corrosion or electrical malfunction;
- corrosion caused by sea air if located near a waterway, beach etc;
- fitment to a commercial door or in a commercial operating application, installation of a residential garage door opener in a commercial or industrial premises other than a single-family dwelling;
- lack of proper maintenance, service or care of the door and/or Unit; and/or
- damage caused by insects, pests or other after sale damage caused by events or accidents outside Chamberlain's reasonable control and not arising under normal and standard operating conditions.

#### 5 Where you need help with our product

If you have a problem with the Unit or if you are concerned it may be defective, please contact our Customer Service team below:

|                    |                                                                                            |
|--------------------|--------------------------------------------------------------------------------------------|
| <b>Australia</b>   | Phone toll free 1800 638 234                                                               |
| Fax toll free      | 1800 888 121                                                                               |
| Address            | Suite G.02, City Views Business Park, 65 Epping Rd Macquarie Park NSW 2113                 |
| Email              | <a href="mailto:customerservice@chamberlainanz.com">customerservice@chamberlainanz.com</a> |
| Website            | <a href="http://www.gomerlin.com.au">www.gomerlin.com.au</a>                               |
| <b>New Zealand</b> | Phone toll free 0800 653 667                                                               |
| Auckland           | Phone 09 477 2823                                                                          |
| Fax toll free      | 0800 653 663                                                                               |
| Email              | <a href="mailto:customerservice@chamberlainanz.com">customerservice@chamberlainanz.com</a> |
| Website            | <a href="http://www.gomerlin.co.nz">www.gomerlin.co.nz</a>                                 |

As a first step, our Customer Service team will provide product support assistance to help you try to resolve the problem and in some cases, replacement parts for "do it yourself repairs". If our technical team need to see the product to determine the nature of the fault, we will arrange an inspection by an experienced technician, or ask that you send the product to us.

If your product was installed at your premises by an authorised installer, please contact the installer indicated in your sales documents for prompt on-site service, or consult our Customer Service team if you need help in finding a local service technician. A service fee for on-site service may apply.

Authorisation from Chamberlain is required for warranty service under this Limited Warranty.

#### 6 Delivery Charges

If an inspection is required in order to determine the nature of the fault, please send the Unit freight paid and well packaged in accordance with our instructions. Any costs associated with transporting the Unit will be at Chamberlain's cost if the Unit has breached a statutory consumer guarantee. Repairs and replacement parts provided under this Limited Warranty are free of charge (and repaired items or replacement parts for Units found to be defective will be returned to you at our cost), and warranted by Chamberlain for the remaining portion of the original warranty period. However, if you make a claim under this Limited Warranty, and this Limited Warranty does not apply, or if the law does not provide you with a statutory right or remedy as a consumer, you may be required to pay labour, assessment and/or freight costs and delivery charges to repair, replace and/or return the Unit to you.

#### 7 How to register your product

Please register your Unit and contact details at this link [www.gomerlin.com.au/warranty-registration/](http://www.gomerlin.com.au/warranty-registration/) for Australia, or [www.gomerlin.co.nz/register-your-warranty/](http://www.gomerlin.co.nz/register-your-warranty/) for New Zealand, so that we or your authorised installer can locate your details and provide you with product support assistance as quickly as possible, and keep you up to date with product updates. Registration can also be done by contacting Chamberlain Customer Service.

#### 8 Important Reminder

All other guarantees (other than your statutory rights and guarantees as a consumer under applicable laws) are excluded to the fullest extent that we may lawfully do so. Unless the law requires us to do so, we do not accept any other liability, such as compensation for damages, injury or loss.

Last updated: [28th January 2026]